



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

ब्यांगडाडा, भूपा,



कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

कोशी प्रदेश, नेपाल

आ.व. ०८०/८१

च.नं.

मिति:-२०८०/११/१०

श्री फर्म/कम्पनीहरु सबै ।

बिषय:- लागत अनुमानका लागि दररेट उपलब्ध गराउने सम्बन्धमा ।

उपरोक्त बिषयमा यस शिवसताक्षी नगरपालिका नगर कार्यपालिकाको कार्यालयहरूलाई CC Camera जडानका लागि निम्न उपकरणहरूको आवश्यकता परेको हुदाँ उक्त सामग्री खरिद तथा जडानका लागि लागत अनुमान तयार गर्नुपर्ने भएकोले पत्र मितिले ७ दिन भित्र दररेट उपलब्ध गराईदिनु हुन सार्वजनिक सूचना प्रकाशन गरिएको व्यहोरा अनुरोध छ ।

निम्न:-

Technical Specification of CC Camera and accessories

1. CC Camera

SN	Parameters	Requirements	Qty	Unit
1	Camera			
	Image Sensor	1/1.2" Progressive Scan CMOS		
	Max. Resolution	3840 × 2160		
	Shutter Speed	1/3 s to 1/100,000 s		
	Wide Dynamic Range	130 dB		
	Angle Adjustment	Pan: 0°to 355°, tilt: 0°to 90°, rotate: 0°to 360°		
2	Lens			
	Depth of Focus	2.8 mm: 4.5 m to ∞ 4 mm: 7 m to ∞ 6 mm: 13 m to ∞		
3	DORI			
	DORI	2.8 mm, D: 96 m, O: 38 m, R: 19 m, I: 10 m 4 mm, D: 102 m, O: 41 m, R: 21 m, I: 11 m 6 mm, D: 167 m, O: 66 m, R: 33 m, I: 16 m		




शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३

फ्याक्स ०२३-४७०३२२



कोशी प्रदेश, नेपाल

आ.व. ०८०/८१

च.नं.

4	Illuminator		1	Pic
	White Light Range	60 m		
	Smart Supplement Light	Yes		
5	Video		1	Pic
	Main Stream	50 Hz: 25 fps (3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 24 fps (3840 × 2160) 30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)		
	Sub Stream	50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360) 60 Hz: 30 fps (1280 × 720, 640 × 480, 640 × 360)		
	Third Stream	50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360) 60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)		
	Video Compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264		
	Video Bit Rate	32 Kbps to 16 Mbps		
	Bit Rate Control	CBR/VBR		
	Region of Interest (ROI)	1 fixed region for main stream and sub-stream		
6	Network		1	Pic
	Simultaneous Live View	Up to 6 channels		
	Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets		
	Security	Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2, WSSE and digest authentication for Open Network Video Interface		
Network Storage	NAS (NFS, SMB/CIFS), auto network replenishment (ANR)			
7	Image		1	Pic
	Day/Night Switch	Day, Night, Auto, Schedule		
	Image Enhancement	BLC, HLC, 3D DNR		
	Image Parameters Switch	Yes		

[Handwritten signature]

[Handwritten signature]
सत बहादुर राई
नगर कार्यपालिका अधिकारी




शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३

फ्याक्स ०२३-४७०३२२



कोशी प्रदेश, नेपाल

आ.व. ०८०/८९

च.नं.

	Image Settings	Rotate, mirror, privacy mask, saturation, brightness, contrast, sharpness, gain, white balance adjustable by client software or web browser
8	Interface	
	On-board Storage	Built-in memory card slot, support microSD/microSDHC/microSDXC/TF card, up to 512 GB
	Hardware Reset	Yes
	Communication Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
9	Event	
	Basic Event	Motion detection (human and vehicle targets classification), video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error)
	Smart Event	Scene change detection
	Linkage	Upload to FTP/memory card/NAS, notify surveillance center, trigger record, trigger capture, send email
10	Deep Learning Function	
	Face Capture	Yes
	Perimeter Protection	Line crossing, intrusion, region entrance, region exiting Supports human and vehicle targets classification
11	General	
	Power	12 VDC \pm 25%, 0.7 A, max. 8.5 W, \varnothing 5.5 mm coaxial power plug, reverse polarity protection PoE: (802.3af, Class 3, 36 V to 57 V), 0.27 A to 0.17 A, max. 9.5 W
	General Function	Anti-flicker, heartbeat, password reset via e-mail, pixel counter
	Software Reset	Yes
12	Approval	
	EMC	FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 50130-4: 2011 +A1: 2014); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 7)


[Handwritten signature]

[Handwritten signature]
अनंत बहादुर राई
प्रशासकीय अधिकृत



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय



कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

कोशी प्रदेश, नेपाल

आ.व. ०८०/८१

च.नं.

Safety	UL (UL 62368-1); CB (IEC 62368-1:2014+A11) CE-LVD (EN 62368-1:2014/A11:2017)		
--------	------------------------------------------------------------------------------------	--	--

2. Video Surveillance Monitor

SN	Parameters	Requirements	Qty	Unit	
1	Display	Screen Size	55"	1	Pic
		Active Display Area	1209.6 (H) mm × 680.4 (V) mm		
		Resolution	3840 × 2160@60 Hz		
		Backlight	LED		
		Pixel Pitch	0.315 (H) mm × 0.315 (V) mm		
		Brightness	350 cd/m ²		
		Viewing Angle	178°(H)/178°(V)		
		Color Depth	8 bit		
		Contrast Ratio	1200:1		
		Response Time	8 ms		
		Refresh Rate	60 Hz		
		Reliability	7 × 24 H		
Color Gamut	72% NTSC				
2	Interface	Video & Audio Input	HDMI 1.4 × 1, HDMI 2.0 × 1, VGA × 1, Audio in × 1		
		Video & Audio Output	Speaker (6 Ω 7 W) × 2		
		Data Transmission Interface	USB × 1		
3	Power	Power Supply	100~240 VAC, 50/60 Hz		
		Power Consumption	≤ 145 W		
		Standby Consumption	≤ 0.5 W		
4	Working Environment	Working Temperature	0 °C to 40 °C (32 °F to 104 °F)		
		Working Humidity	20% to 80% RH (Non-Condensing)		
		Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)		
		Storage Humidity	10% to 90% RH (Non-Condensing)		
5	General	Casing Material	Plastic		
		VESA	200 mm × 200 mm (4 × M6 mm)		
		Bezel Width	8.24 mm (top/left/right), 20.69 mm (bottom)		

1/10/20

शिवसताक्षी नगरपालिका
कार्यालय




शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

ब्यांगडाडा, भापा

कोशी प्रदेश, नेपाल



आ.व. ०८०/८१

च.नं.

3. Flash Light

SN	Parameters	Requirements	Qty	Unit
General				
1	Light Type	IR light	1	Pic
	IR Wavelength	≥850nm		
	Effective Distance	16 to 25 m		
	Response Time	≤ 67 ms		
	Color Temperature	5500 K ± 500 K		
	Trigger Manner	TTL level (switch trigger optional)		
	Flash Energy	200 J		
	Service Life	≥ 20 million Times		
	Coverage	1 lane(s)		
	Power	AC 220V±10% , 48Hz to 52Hz		
	Weight	Approx. 3.5 kg (7.72 lb.)		
	Operating Condition	-25 °C to 70 °C (-13 °F to 158 °F). Humidity: 5% to 90% (non-condensing)		
Consumption	Average < 100 W (@ 1 flash / s), max < 300 W			
Approval				
2	Protection	IP65: IEC 60529: 1989+A1: 1999+A2: 2013		

4. Battery and Battery Management System.

SN	Parameters	Requirements	Qty	Unit
General				
1	Nominal Capacity	50A		
	Typical Voltage	14.4V LF280K		
	Charge/discharge cut-off voltage	14.6V/2.5V		
	AC impedance resistance (1KHz)	<0.25mQ.		
	Continuous charge/discharge	1C/1C		
	Charging Temperature	0C°~55C°		
	Discharge tempature	-20C°~55C°		
	Weight	10.84±0.3KG		
	Dimension	173*71*204mm		
BMS (Battery Management System)				
2	Charge Current	15 Amps max		

[Handwritten signature]

[Handwritten signature]
शिवसताक्षी नगरपालिका
कोशी प्रदेश, नेपाल




शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

कोशी प्रदेश, नेपाल



आ.व. ०८०/८९

च.नं.

Discharge Current	30 Amps max	1	Pic/ Set
Charge Voltage	14.6 Volt		
Cable Size (AWG)	12		
Dimensions	80mm x 60mm x 10mm		
Weight (gm)	83 grams		
Over Discharge Detect	2.2V ±0.1		
Over Discharge Release	2.7V ±0.1		
Overcharge Detect Voltage	3.75V ±0.05		
Overcharge Release Voltage	3.55±0.05		
Working Current	100 uA(microamps)		
Balance Current	30mA ±5		
Balance Detect Voltage	3.50V		
Working Temperature Range	-20°C to 70°C		

5. Uninterruptible Power Supply Unit

SN	Parameters	Requirements	Qty	Unit
1	DC Output DC Voltage	12V		
	DC Current 30A	30A		
	Ripple & Noise	80MV		
	Channel	4 Unit		
	DC Adjustable Range	+10% Rated Voltage		
	Voltage Tolerance	2.00%		
	Line Regulation	0.50%		
	Load Regulation	1%		
	Setup,Rise Time,Hold Up Time	200ms,50ms, 20ms/230VAC,AC Input AC Voltage Range: 85-264VAC		
	Frequency Range	47-63Hz		
	Efficiency	90%		
	AC Current	0.86/115V0.4A/230V		
	AC Inrush Current	20A/115V 40A/230V		
	Leakage Current	0.5mA/240VAC		
	Protection Over-load	105%-150% hiccup mode,Auto-recovery		
	Over-voltage	115%-135% Cut Off the Output,Auto-recovery		
	Over-temp.	Shut down O/P voltage, Auto-recovery		
	Environment Working temp.	-10~ +60°C (Refer to output load derating curve)		

7/10/2019
2019/10/7


अखण्ड बिजापुर राई
प्रमुख प्रशासकीय अधिकारी



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२



कोशी प्रदेश, नेपाल

आ.व. ०८०/८१

च.नं.

Working Humidity	20 ~ 90% RH, non-condensing	1	Pic
Storage Temp.	-10~ +60C°		
Storage Humidity	10~ 95% RH		
Safety Isolation Resistance	I/P-O/P, I/P-FG, O/P-FG: 100M Ohms/S00VDC / 25C*/ 70% RH		
Withstand Voltage	I/P-O/P: 3KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC		
Safety standards	CE, RoHS, FCC		

6. Miniature Circuit Breaker

SN	Parameters	Requirements	Qty	Unit
1	Breaking Capacity	6KA	1	Pic
	Rated Voltage	90-295V		
	Rated Current	1-50A Adjustable		
	BCD Curve	c		
	Rated Frequency (Hz)	50/60Hz		
	Number of Pole	1		
	Protection	Other		
	Function1	Over Load protect		
	Function2	Over Current Protect		
	Certificate	CE		

7. CCTV Vertical Pole Mount Bracket

SN	Parameters	Requirements	Qty	Unit
1	Weight	Approx. 1500 g (3.31 lb.)	1	Pic
	Appearance	White		
	Material	Stainless Steel		
	Dimension	127 mm × 46 mm × 250 mm (5" × 1.81" × 9.84")		
	Description	Horizontal Pole Mount		

8. Optical Network Unit

Technical specification of Optical Network Unit (ONU)			Qty	Unit
S.N	Parameter	Description		

[Handwritten signature]

[Handwritten signature]
प्रमुख प्रशासकीय अधिकारी



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३

फ्याक्स ०२३-४७०३२२

ब्यांगडाडा, भापा,

कोशी प्रदेश, नेपाल

आ.व. ०८०/८१

च.नं.



1	Fiber port	1 GPON interface, SC single-mode/single-fiber, Downstream rate 2.5Gbps, Upstream rate 1.25Gbps	1	Pic
	Wavelength	Tx 1310nm, Rx 1490nm		
	Fiber interface	SC/PC		
	RS sensitivity	<-28dBm (1490nm)		
	LAN	1*10/100/1000Mbps adaptive Ethernet ports, full/half duplex, RJ45 interface		
	Throughput	Throughput can reach 900Mbps or more		
	DC power	12V 1A, external AC-DC power adapter		
	Button	Reset, power		
	Power	≤8W		
	Operation	Working temperature: -5-+55°C working humidity: 10-90%(non condensation)		

9. Electric Power Cable

S.N	Parameter	Description	Qty	Unit
1	General			
	Type of cable	2XWY		
	Voltage Grade V	1100		
	No of cores X size in sqmm	3 x 10		
2	Conductor			
	Material	Plain annealed Copper as per Class 2 of IS:8130/2013		
	Max d.c resistance of conductor at 20° C (ohm/km)	1.83		
	Shape of conductor	Stranded Circular		
3	Insulation			
	Material	XLPE as per IS 7098(Pt-1)/88, Latest		
	Nominal thickness (mm)	0.7		
	Core Identification	Red, Yellow and Blue		
Inner Sheath				
4	Material	0.3		
	Minimum thickness (mm)	Extruded PVC Type ST2 as per IS:5831/84		
5	Armoring			
	Material	Galvanised Steel		
	Type of armoring	Round Wire		

Handwritten signature

अध्यक्ष
प्रमुख प्रशासकीय अधिकृत



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

ब्यांगडाडा भूपा,

कोशी प्रदेश, नेपाल

आ.व. ०८०/८९

च.नं.



	Nominal size of armor (mm) ± 0.040	1.4	1	Meter
6	Outer Sheath			
	Material	Extruded PVC Type ST2 as per IS:5831/84		
	Thickness (mm)	1.24 Min		
Color of Outer sheath	Black			

10. surveillance hard disk Drive

S.N	Parameters	Requirements	Qty	Unit
1	General		1	Pic
	Form factor	3.5-inch		
	Interface	6.0 Gbit/s		
	Capacity	10 TB		
	Rotational Vibration (RV) Sensors	yes		
	Shock Sensor	yes		
	Advanced Format (AF)	yes		
	RoHS compatible	yes		
	Halogen free	yes		
Recording Technology	CMR			
2	Performance		1	Pic
	Rotational speed (rpm)	7200		
	Max. data transfer speed (sustained MB/s Typ.)	248		
	Buffer size (MB)	256		
3	Reliability		1	Pic
	Average latency (ms)			
	Workloads (TB/year)	180		
	MTTF (hours)	1000000		
	Unrecoverable error rate	1 per 10 ¹⁴		
24 x 7 operation	yes			
Load/Unload cycle	600000			
Limited warranty (years)	3			
4	Power Management		1	Pic
	Supply voltage	5 V DC +6/-5 % 12 V DC ±10 %		
	Consumption (operating)	9.48 W typ.		
	Consumption (active idle)	7.15 W typ.		
5	Environmental			

Handwritten signature and date: 7/10/2023

अमर चौधरी राई
प्रमुख प्रशासकीय अधिकारी




शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

कोशी प्रदेश, नेपाल



आ.व. ०८०/८१

च.नं.

	Temperature (operating/non operating)	0 to 70 °C -40 to 70 °C
	Vibration (operating)	7.3 2.45
	Vibration (non-operating)	29.4 m/s ² {3.0 G} (5 to 500 Hz)
	Shock (operating)	686 m/s ² {70 G} (2 ms duration)
	Shock (non-operating)	2450 m/s ² {250 G} (2 ms duration)
	Acoustics (idle mode)	34 dB typ.
6	Physical	
	Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm

11. Manageable Switch

S.N	Parameter	Description	Qty	Unit	
1	Manageable Switch	10/100/1000Base-T ports	24	1	Pic
		SFP ports	4		
		Layer Type	Layer 2		
		Switching capacity	56 Gbps		
		Forwarding rate	41.67 Mpps		
		Packet Buffer	4.1 Mbit		
		MAC address table	8,000		
		Maximum VLAN Support	4094		
		Operating Temperature	0°C to 50°C (32°F to 122°F)		
		Storage Temperature	-40°C to 70°C (-40°F to 158°F)		
		Jumbo Frame	9216		
		Flow Control	✓		
		STP (IEEE 802.1d)	✓		
		RSTP (IEEE 802.1w)	✓		
		VLAN Range	1-4094		
Port-based VLAN	✓				
MAC-based VLAN	✓				
IP-based VLAN	✓				

Handwritten signature

अमृत बस्नेत राई
प्रमुख प्रशासकीय अधिकृत




शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

ब्यांगडाडा, भापा,

कोशी प्रदेश, नेपाल



आ.व. ०८०/८१

च.नं.

12. Junction Box

S.N	Parameter	Description	Qty	Unit
1	Junction Box	Electric Junction Box	1	Pic
2		Outdoor ABS PC Plastic Pole Mount Electronic Housing IP65-IP66 Waterproof CCTV Junction box for installing CCTV accessories	1	Pic
3		Outdoor ABS PC Plastic Pole Mount Electronic Housing IP65-IP66 Waterproof CCTV Junction box for Power supply unit and LifeP04 Battery	1	Pic

13. Patch Cable

S.N	Parameter	Description	Qty	Unit
1	Patch Cable	Length: 3M Speed: Upto 5Gbps 802.3bz/ab/u Stable Frequency: upto 250 MHz Insulation: HDPE over Copper, FR-PVC Jacket Color: Any	1	Pic

14. Iron Pole

S.N	Parameter	Description	Qty	Unit
1	Pole	Type: Iron Length: 6M Diameter: 6 inch Color: Yellow	1	Pic

15. Spiral Cable

S.N	Parameter	Description	Qty	Unit
1	Cable	Style: Outdoor Spiral Material: Polyethylene Length: 3 M Color: Any	1	Pic

16. Drop Cable

S.N	Parameter	Description	Qty	Unit
1	Drop Cable	Core: single	1	Pic

Handwritten signature

Handwritten signature
प्रमुख प्रशासकीय अधिकारी



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२



कोशी प्रदेश, नेपाल

आ.व. ०८०/८९

च.नं.

		Fiber Core Material: PMMA Cladding Material: Fluorinated Polymer Jacket: PE/PVC Numerical Apertuer: 0.5		
--	--	----------------------------------------------------------------------------------------------------------------------------------------------	--	--

17	Leased	Optical Fiber Leased	1	Meter
18	Installation	Network Camera	1	Pic
		ANPR Flash Light	1	Pic
19	Annual Cost	Network Camera Annual Maintenance Cost	1	Pic
		Annual Optical Fiber Leased Cost	1	Meter

निम्न Format मा दररेट उपलब्ध गराईदिनु हुन अनुरोध छ ।

SN	Particular	Qty	Unit	Rate	Total	Remark
1	8 MP 4 K ColorVu Fixed Bullet Network Camera	1	pcs			
2	CCTV Vertical Pole Mount Bracket	1	pcs			
3	10 TB Video Surveillance Hard Disk Drive	1	pcs			
4	55" Video Surveillance Monitor	1	pcs			
5	24-Port Gigabit, 4 SFP Slots L2 Cloud Managed Switch	1	pcs			
6	ANPR Flash Light	1	pcs			
7	Optical Network Unit	1	pcs			
8	Optical Fiber Drop Patch Cable	1	pcs			
9	Electricity Cable 10mm	1	meter			
10	12V/20A/8-CH Uninterruptible Power Supply Unit	1	pcs			
11	12V 25Ah LiFePO4 Battery & Battery Management System	1	pcs			
12	Electricity Junction Box	1	pcs			
13	10kA 16A Smart MCB DP	1	pcs			
14	Outdoor ABS PC Plastic Pole Mount Electronic Housing IP65-IP66 Waterproof CCTV Junction Box for installing CCTV accessories	1	pcs			
15	Outdoor ABS PC Plastic Pole Mount Electronic Housing IP65-IP66 Waterproof CCTV Junction Box for installing Power Supply Unit & LiFePo4 Battery	1	pcs			
16	Outdoor 3M CAT6 Network Patch Cable	1	pcs			

Handwritten signature

अमर बहादुर राई
प्रमुख प्रशासकीय अधिकृत



शिवसताक्षी नगरपालिका

नगर कार्यपालिकाको कार्यालय

कार्यालय ०२३-४७०३२३
फ्याक्स ०२३-४७०३२२

ब्यांगडाडा, भोजपुर
२०७३
शिवसताक्षी नगरपालिका
कार्यपालिकाको कार्यालय
ब्यांगडाडा, भोजपुर
कोशी प्रदेश, नेपाल
२०७३

कोशी प्रदेश, नेपाल

आ.व. ०८०/८९

च.नं.

17	3M Outdoor Sprial Cable Warper	1	pcs		
18	Network Camera Installation Cost	1	sites		
19	ANPR Flash Light Installation Cost	1	sites		
20	6 Meter Iron Pole with Installation Cost	1	set		
21	Optical Fiber leased	1	meter		
22	Network Camera Annual Maintenance Cost	1	sites		
23	Annunal Optical Fiber Leased Cost	1	meter		
	Total				
	VAT				
	Grand Total				

[Handwritten signature]

[Handwritten signature]
अमृत बहादुर राई
प्रमुख प्रशासकीय अधिकृत